

**Part Number: 26501D**

**General:**

- Number of decks: 1
- Number of positions: Up to 8 (adjustable)
- Schematic - see contact table
- Handle: D (Pistol Grip)

**Electrical:**

\* RATINGS:

- 25A/120 VAC
- 15A/600 VAC
- 20A/600 VAC Resistive
- 3A/125 VDC
- 1A/250 VDC



- \* Current carrying capacity: 25 amperes
- \* Dielectric Withstanding Voltage: 2200 Vrms
- \* Contact Resistance: Initial, 10 milliohms max.
- \* Insulation Resistance: 100 Megohms min., initial



**Mechanical:**

- \*Type Acton: Non-Shorting
- \* Indexing: 45° positive detent
- \* Rotational Life: 65,000 operations

**Materials and Finishes:**

- \* Rotors and Stators: Thermoset Plastic, UL 94VO
- \* Rotor contacts: Phosphor bronze
- \* Stator contacts: Silver plated copper, screw type
- \* Terminal hardware: silver plated brass
- \* Exterior Metal: Steel with zinc chromate finish
- \* Knob: thermoset phenolic

DECK	CONTACTS	POS.							
		1	2	3	4	5	6	7	8
1	11 0-1-1-1-0 13	X				X			
	12 0-1-1-1-0 14		X				X		
	13 0-1-1-1-0 15			X				X	
	14 0-1-1-1-0 16				X				X
	15 0-1-1-1-0 17	X				X			
	16 0-1-1-1-0 18		X				X		
	17 0-1-1-1-0 11			X				X	
	18 0-1-1-1-0 12				X				X



**HANDLE TYPE: PISTOL GRIP**

