


Technical data:

Handle Material:	Red GF Nylon 6
Upper Housing Material:	Zinc Diecast
Lower Housing Material:	GP Phenolic
Min. Insulation Resistance:	100 Mohm
Dielectric Withstanding Voltage:	1,100V -1min
Voltage Drop Max.:	0.175 mV
Voltage:	48 VDC
Continuous Rating:	300 A
Overload:	1,100 A - 240sec. 1,500 A - 90sec. 2,000 A - 30sec
Sealing:	IP67
Vibration:	4G / 50-2KHz
Shock:	6G / 11ms
Temperature Range:	-40C to +85C
Terminal Torque:	155 in.lb
Mounting Torque:	18 ft.lb

TERMINAL TAG



PRODUCT LABEL
500S-300 YYWW
48VDC-300AMPS
SHALCO

UPC BARCODE
5 TYP.
1.5 TYP.

PROPRIETARY AND CONFIDENTIAL
This document contains proprietary data for products designed by Shallco, Inc., of Smithfield, NC. No disclosure, reproduction, or use of any part thereof may be made except by written permission.

REV.	DESCRIPTION	DATE	APP'D
	REVISIONS		

	NAME	DATE
DRAWN	JRT	4-15-15
CHECKED		
ENG APPR.	RMF	4-15-15
MFG APPR.		
Q.A.		

DIMENSIONAL TOLERANCES:
FRACTIONAL: ± 1/32
ANGULAR: MACH ± 1.0 BEND ± TWO PLACE DECIMAL : ±0.020
THREE PLACE DECIMAL: ±0.010

SHALCO
308 COMPONENTS DRIVE, SMITHFIELD, NC 27577 USA
DO NOT SCALE DRAWING
TITLE: **BATTERY SWITCH 48VDC-300AMP**
MATERIAL: SEE TECHNICAL DATA FINISH: SEE TECHNICAL DATA
BLANK WEIGHT: N/A PART WEIGHT: 0.75 LBS
SIZE **A** DWG. NO. **500S-300** REV. **D**
SCALE: 1:1.5 SHEET 1 OF 1

DWG NO: 500S-300